

# BOOTSTRAP

It is a framework that offers responsive design. It has pre-styled element.

class	description
container	provides <sup>responsive</sup> fixed width container
container-fluid	a full width container
col	column in making grid
text-center	center-aligned text
text-lowercase	to show lowercase text
text-uppercase	to show uppercase text
text-capitalize	to indicates capitalize text
font-italic	italic text
font-weight-bold	bold text
font-weight-bolder	bolder text

## Colors

text-muted	<del>bg-muted</del>
text-primary	bg-primary
text-success	bg-success
text-info	bg-info
text-warning	bg-warning
text-danger	bg-danger
text-secondary	bg-secondary
text-white	bg-white-50
text-dark	bg-dark <sup>opacity</sup>
text-light	bg-light

These are called contextual class

# Tables

table	adds basic styling to a table
table-stripped	adds zebra stripes to table
table-bordered	adds borders on all side of table and cells
table-hover	adds a hover effect (gray background) on table rows
table-dark	adds a dark background to table
table-success	
table-info	
table-primary	
table-borderless	removes borders from table
Contextual class	are used to color the whole table.
table-responsive	adds a scrollbar to the table when needed
thead-dark	to color the header black

Note - You can also use contextual class in tr td tag.

```
ex - <tr class="table-success">  
      <td> Raj </td>  
      <td> Gupta </td>  
      <td> 20 </td>  
</tr>
```

## Image

Use in `img` tag to design image.

- `rounded` add rounded corners to an image
- `rounded-circle`
- `img-thumbnail` shrinks the image to a thumbnail (bordered)

## Alerts

Bootstrap provides an easy way to create predefined alert message using given class.

- `alert` to create an alert message
- `alert-success`
- `alert-primary` } to style
- `alert-dark`
- `alert-info`

### Closing alerts-

add an `alert-dismissible` class to the `alert-container`. then add `class="close"` and `data-dismiss="alert"` to a link or a button. You can also use `fade` and `show` classes to add a fading effect while closing the alert message.

```
Ex- <div class="alert alert-info alert-dismissible  
fade show">  
<button type="button" class="close"  
data-dismiss="alert"> &times; </button>
```

```
<strong> Alert! </strong>  
<p> There is a new message </p>  
</div>
```

### Buttons

Button classes are used to design <a> and <button> tag

- btn
- btn-primary
- btn-info
- btn-dark
- btn-success
- btn-outline-primary
- btn-outline-info
- btn-outline-danger
- btn-outline-success
- btn-lg
- btn-sm
- btn-block
- active

} to add bg-color

} to design border

disabled class is used only with links and disabled attribute is used with buttons

class used with button container

btn-group - used to group a series of button or links on a single line

- btn-group-lg
- btn-group-sm

### btn-group-vertical

To create dropdown list or nav

btn-group

dropdown-toggle used in dropdown container with an attribute data-toggle="dropdown"

dropdown-menu used in creating dd menu

dropdown-item

```
Ex <div class="btn-group">  
  <button type="button" class="btn btn-  
  primary dropdown-toggle" data-toggle="dropdown">  
  dropdown  
  </button>  
  <div class="dropdown-menu">  
    <a class="dropdown-item" href="#">  
    Hi </a>  
    <a class="dropdown-item" href="#">  
    Gi </a>  
  </div>  
</div>
```